

# Safety-interlocked Power Outlet

### 32A 480VAC

Catalog No: R32-480-30-65SNQP-SP


Item No: 1706-59ANP






- UL Listed safety-interlocked power outlet containing an integral 30A circuit breaker
- Actuator rod allows user to turn on/off and reset tripped breaker
- UL Listed circuit breaker rated 65kAIC
  @ 480VAC provides short circuit & over current protection
- "Power On" LED indicator light (shown as energized)
- 2-piece receptacle with polyamide receptacle housing and high temp rynite® insert
- Spring-loaded snap cover protects receptacle when not in use
- Interlocked replacement outlet for use in ESL single gang or multi gang assemblies to power ISO reefer containers

#### Drawing



**FRONT VIEW** 



SIDE VIEW

## **Approvals**

- UL/cUL Listed outlet
- UL 489 Listed / CSA certified molded case circuit breaker



# Specifications

Catalog No: R32-480-30-65SNQ-SP

Item No: 1706-59ANP

Ratings				
	Receptacle	32A 480VAC (380/440VAC 50/60 Hz) 3h per IEC 60309-1 & -2		
	Circuit breaker	3P molded case, 30A trip / 65,000AIC @ 480VAC, other trip and AIC ratings available - contact factory		
	Terminals	Installer wires direct to circuit breaker: (3) phase & (1) ground pressure type screw terminals, Phases: #14 AWG - 2/0 (2.5 - 70mm²) wire range, Ground: #14 - #6 AWG (2.5-16mm²) wire range		
	Environmental	Type 4X when housed in ESL single gang or multi gang assembly		
Materials				
	Stainless steel	Frame, faceplate, on/off rod, snap cover, interlock mechanism, contact terminal screws & spring, and all fasteners		
	Nickel plated brass	Contact sleeves		
	Rynite®	Receptacle insert		
	Polyamide	Receptacle housing, screw cover (optional)		
	GP Acetal	Knob, rod seal holder		
	Neoprene (CR)	Gaskets, cover seals		
	Buna-N (Nitrile/NBR)	O-rings		
Packaging				
	Product weight	7 lbs.		
	Shipping weight	8 lbs.		
	Shipping dimensions	16in x 8in x 8in		
Replacement Parts	Description	Item No.	Description	Item No.
	Stainless steel snap cover assembly	1500-01	Ground sleeve kit	4016-03
	Receptacle complete housing with insert, contact sleeve & ground assembly	4010-75	Phase sleeve kit (set of 3)	4015-01
	Insert, contact sleeve & ground assembly	4010-76	Pilot light kit	4090-35GNH
	Circuit breaker kit	4020-110		