

## 18-Gang Pad Mount Assembly

### 32A 480VAC

(32A 380/440VAC per IEC 60309-1 & -2)

Catalog No: E18-R32-480-30-22SND-SP


Item No: 2223-67


#### **Features**




- UL Listed 18-gang assembly complete with UL Listed safety-interlocked outlets each containing an integral 30A circuit breaker
- Type 4x enclosure manufactured from 14GA seamwelded stainless steel (powder-coated grey)
- (18) safety-interlocked ESL outlets #1700-56AN factory wired to power distribution block (PDB)
- UL Listed circuit breaker rated 22kAIC @ 480VAC provides short circuit & overcurrent protection at each outlet
- Each oultet's actuator rod allows user to turn on/off and reset tripped breaker
- PDB accepts incoming cable range of (2) #6AWG -350kcmil per phase line side
- Includes 500A main circuit breaker with gasketed bolt-on access cover

#### Drawing







#### **Approvals**

- UL/cUL Listed modules and assembly
- UL 489 Listed / CSA certified molded case circuit breakers



# **Specifications**

Catalog No: E18-R32-480-30-22SND-SP

Item No: 2223-67

| Ratings              |   |   |                   |          |
|----------------------|---|---|-------------------|----------|
|                      | 18-Gang assembly                          | 500A 480VAC (380 - 480VAC 50/60hz) 3 phase 3 wire + ground, 22kAIC RMS symmetrical amps   |                   |          |
|                      | Receptacles                               | 32A 480VAC (380/440VAC 50/60 Hz) per IEC 60309-1 & -2   |                   |          |
|                      | Circuit breakers                          | 30A trip, 22,000AIC @ 480VAC, other trip and AIC ratings available - contact factory  |                   |          |
|                      | Environmental                             | Type 4X/IP66  |                   |          |
|                      | PDB terminals                             | Line side terminals accept (2) #6 - 350kcmil per phase<br>Ground terminal accepts (12) #14 - #4AWG  |                   |          |
| Materials            |   |   |                   |          |
|                      | Stainless steel                           | Enclosure, access cover, outlet frames, on/off rods, interlock mechanisms, contact terminal screws & springs, snap covers and all fasteners |                   |          |
|                      | Aluminum                                  | PDB Lugs  |                   |          |
|                      | Nickel plated brass                       | Contact sleeves   |                   |          |
|                      | Rynite®                                   | Receptacle insert   |                   |          |
|                      | Polyamide                                 | Receptacle housing  |                   |          |
|                      | Buna-N (Nitrile/NBR)                      | O-rings, gaskets, cover seals   |                   |          |
| Approximate Weight   |   |   |                   |          |
| G                    | Approx. weight                            | 320 lbs.  |                   |          |
|                      | Approx. shipping weight                   | 360 lbs.  |                   |          |
| Replacement<br>Parts | Description                               | Item No.  | Description       | Item No. |
|                      | Safety-interlocked power outlet           | 1700-56AN   | Circuit breaker   | 4020-01  |
|                      | Stainless steel snap cover assembly       | 1500-01   | Ground sleeve kit | 4016-03  |
|                      | Receptacle insert contact sleeve assembly | 4010-75   | Phase sleeve kit  | 4015-01  |