

# 20-Gang Modular Reefer Sharing Unit

## 32A 480VAC

(32A 380/440VAC 3h per IEC 60309-1 & -2)

Catalog No: E20-RSUWS-32-480-SP-T


Item No: 3500-02

### Features



- 20 Modular Reefer Sharing Units (RSUs) to alternate power to up to 40 reefers (20 at a time) thereby doubling the frozen load capacity
- 200A fused main disconnect
- Interlocked outlets cannot be energized until plug is mated
- Easy-to-use timer adjustment knob
- Ammeter to monitor total current draw
- Forklift access to allow maximum flexibility for shipboard and landside use
- Heavy-duty stainless steel construction resists corrosion & abuse
- Each modular RSU's protected by a 30A circuit breaker rated 22kAIC at 480VAC

### Drawing



### Approvals

- UL Listed receptacles
- UL Listed plug
- UL 489 Listed / CSA certified molded case circuit breaker

# Specifications

Catalog No: E20-RSUWS-32-480-SP-T

Item No: 3500-02

## Ratings

Receptacle	32A 480VAC (380/440VAC 50/60 Hz) 3 phase 3 wire + ground, per IEC 60309-1 & -2
Circuit breakers	30A Trip, 22,000 AIC @ 480VAC, other trip and AIC ratings available - contact factory
Plug	Appleton® 200A 600VAC 3P, 4W
Main disconnect	Fused 200A
Ammeter	0-500A, 60Hz
Environmental	Type 4X/IP66

## Materials

Stainless steel	Enclosure, access cover, outlet frames, on/off rods, interlock mechanisms, contact terminal screws & springs, snap covers and all fasteners
Aluminum	PDB Lugs
Nickel plated brass	Contact sleeves
Rynite®	Receptacle insert
Polyamide	Receptacle housing
Buna-N (Nitrile/NBR)	O-rings, gaskets, cover seals

## Approximate Weight

Approx. weight	750 lbs.
Approx. shipping weight	790 lbs.