

Safety-interlocked Reefer Outlet Product Selection Information

R32 - 480 - 30 - 22 - S - - D - - SP

Voltage
 240 = 240VAC
 480 = 480VAC

**Circuit Breaker
 Trip Rating**
 30 = 30AMP
 50 = 50AMP
 60 = 60AMP

**Circuit Breaker
 Interrupting Capacity**
 22 = 22,000 AIC
 35 = 35,000 AIC
 65 = 65,000 AIC

Receptacle Rating / Configuration
 R30 = 30AMP
 R32 = 32AMP / IEC 60309-1 & -2 CEE 17 3h
 R60 = 60AMP / ISO
 R50 = 50AMP

Faceplate Size
 S = 5" x 6"
 L = 7" x 8"
 G = 8" x 9.5"
 N = 10.5" x 12"
 M = 10" x 10.5"
 X = 15" x 21"

Optional Features
 Blank = No Options
 P = Pilot Light
 A = Auxiliary Contact
 B = Bell Alarm Contact
 R = Rear Actuated

Receptacle Cover
 SP = Snap Cover
 SW = Screw Cover

Interlock Mechanism Model
 C or D = Mechanically Interlocked
 E = Electrically Interlocked

Receptacle Material
 Blank = Lexan®
 N = Polyamide/Rynite Insert
 SN = 316 Stainless Steel/Rynite Insert

